



29797 Beck Road • Wixom, MI 48393 • 248-668-6400 • Fax 248-668-6464

Technical Bulletin 6-07

Vented Nail Board Insulation / Ventilated Roof Insulation

The Tapco Group's warranty for InSpire roof tiles will remain in effect when the InSpire roof tiles are installed over Vented Nailboard or Ventilated Roof Insulation with roof deck slopes $\geq 4:12$. Construction should be in accordance with Section R806.3 of the 2006 International Residential Code (IRC). The system must have a minimum one inch airspace between the decking and rigid insulation.

Restrictions are as follows:

Vented Nailboard / Ventilated Roof Insulation roof deck sheathing must consist of either nominal 1/2" thick AC grade exterior grade plywood deck, or minimum 15/16" solid wood decking and #30 felt paper for a Class C Fire Rated System. Consult your local InSpire Representative for specific recommendations with regards to the Class A Fire Rated System. The Vented Nailboard / Ventilated Roof Insulation System must be installed to its specific manufacturer specifications.

The Tapco Group is not responsible for any non-roof tile issues associated with this type of attic assembly.

Further, The Tapco Group shall not have any liability under its warranty for:

- a) Any damage to or defects in its roof tiles caused by settlement, movement, distortion, deterioration, cracking or other failure of the roof deck or of the materials used as a roofing underlayment over which its tiles are installed
- b) Any damage caused by mold or mildew growth
- c) Defects, damage, or failure caused by application of its roof tiles not in strict adherence with The Tapco Group's written Application Guidelines